



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 防护等级: IP65
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M20
- 联锁元件:
 - 锁扣方式: 金属单扣
 - 材料: 不锈钢

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M20
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel+TPR

| | | | | | | | | | | | |
|---------------|--------------|------------------|---------|-----------------|------------|---|------|---|--------------|---|-------------------|
| | | | | | | 表面处理 Finish | | - | | 图号 Drawing No. | - |
| | | | | | | 材料 Material | | - | | 产品代号 Part Code | HS10A-SM-1L/S-M20 |
| 标记 Mark | 处数 Number | 变更描述/Description | | 签名 Signature | 日期 Date | 比例 Scale | | 版本 REV. | 重量 Weight | 数量 Qty. | 产品料号 Part No. |
| | | 姓名/Name | 日期/Date | 姓名/Name | 日期/Date | 2:3 | V1.0 | 164g | - | | 产品名称 Part Name |
| 绘图 Drawn | | | | 标准化 Stand. | - | | | | | | |
| 审核 Checked | | | | 批准 Approved | | | | | | | |
| 工艺 Process | - | - | | | | | | | | | |
| | | | | | |   | | All Dimensions in mm Original Size DIN A 4 | |  沈阳思沐源科技有限公司 Shenyang Simuyuan Technology Co., Ltd. | |