



技术参数:

- 插芯:
- 插针数: 8+PE
- 额定电流: 16A
- 额定电压: 500V
- 额定脉冲电压: 6kV
- 污染等级: 3
- 安装金属外壳时: 16A 230/400V 4kV 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗:  $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $>500$

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理:
  - 镀银
  - 镀金
- 接触电阻:  $<1\text{m}\Omega$
- 线径范围:
  - 冷压连接:  $0.14-4\text{mm}^2$  (26-12 AWG)
  - 部分装备情况下可达到 $4\text{mm}^2$

外壳:

- 材料:
  - 塑料外壳: 热塑性塑料
  - 金属外壳: 金属

联锁元件:

- 塑料外壳: 聚酰胺 (尼龙)
- 金属外壳: 不锈钢

外壳密封: 丁腈橡胶

- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$

- 依据UL 94的阻燃等级:

- 塑料外壳: V0
- 防护等级: IP65 (联锁状态, IEC 60529)

- 附件:

- 保险延迟针: CESM-1.0R/CESM-1.5R/CESM-2.5R
- 冷压钳: TL02G(0.5-4mm<sup>2</sup>) TL02(0.14-0.37mm<sup>2</sup>)
- 退针器: TL01
- 编码元件: CODE-E

Technical specification:

Inserts:

- No. of contact: 8+PE
- Rated current: 16A
- Rated voltage: 500V
- Rated impulse voltage: 6kV
- Pollution degree: 3
- Mounted metal hood: 16A 230/400V 4kV 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance:  $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles:  $>500$

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface:
  - Hard-silver plated
  - Hard-gold plated
- Contact resistance:  $<1\text{m}\Omega$
- Wire gauge:
  - Crimp terminal:  $0.14-4\text{mm}^2$  (26-12 AWG)
  - partly loaded up to  $4\text{mm}^2$  is possible

Hoods/Housings:

- Material:
  - Plastic hoods/housings: thermoplastic
  - Metal hoods/housings: metal
- Locking element:
  - Plastic hoods/housings: polyamide
  - Metal hoods/housings: stainless steel

- Hoods/Housings seal: NBR
- Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Degree of protection: IP65 (acc.to IEC 60529 for coupled connector)

- Accessories:

- Relay contacts: CESM-1.0R/CESM-1.5R/CESM-2.5R
- Crimping tool: TL02G(0.5-4mm<sup>2</sup>) TL02(0.14-0.37mm<sup>2</sup>)
- Contact removal tool: TL01
- Coding element: CODE-E

					表面处理 Finish	-			图号 Drawing No.	-
					材料 Material	-			产品代号 Part Code	HQ-008/0-MC
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.
		姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.
绘图 Drawn				标准化 Stand.	-	-	1:1	V1.0	15.8g	-
审核 Checked										
工艺 Process	-	-		批准 Approved					All Dimensions in mm Original Size DIN A 4	

