



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 防护等级: IP67 (联锁状态, IEC 60529)
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M50

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Degree of protection: IP67  
(acc.to IEC 60529 for coupled connector)
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M50

|               |              |                  |                |                |         |             |            |                   |            |  |  |
|---------------|--------------|------------------|----------------|----------------|---------|-------------|------------|-------------------|------------|--|--|
|               |              |                  |                | 表面处理<br>Finish |         | -           |            | 图号<br>Drawing No. |            | -  |  |
|               |              |                  |                | 材料<br>Material |         | -           |            | 产品代号<br>Part Code |            | HS32B-T0-4B-M50                                      |  |
| 标记<br>Mark    | 处数<br>Number | 变更描述/Description |                | 姓名/Name        | 日期/Date |             |            | 产品料号<br>Part No.  |            |  |  |
| 绘图<br>Drawn   |              | 姓名/Name          | 日期/Date        | 姓名/Name        | 日期/Date | 比例<br>Scale | 版本<br>REV. | 重量<br>Weight      | 数量<br>Qty. | 产品名称<br>Part Name                                    |  |
| 审核<br>Checked |              |                  |                |                |         | 2:3         | V1.1       | 428g              | -          | -  |  |
| 工艺<br>Process |              |                  | 批准<br>Approved |                |         |             |            |                   |            | 沈阳思沐源科技有限公司<br>Shenyang Simuyuan Technology Co., Ltd |  |