


产品代号 Part code	产品料号 Part NO.	重量/Weight			线径/Wire Gauge		剥线长度 Stripping length
		g	mm <sup>2</sup>	AWG	d	D	
CCSM-1.5		2.98	1.5	16	1.75	3	9
CCSM-2.5		3.08	2.5	14	2.25	3.5	9
CCSM-4.0		3.1	4	12	2.85	3.9	9.6
CCSM-6.0		3.18	6	10	3.5	5	9.6




技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 40A
- 接触电阻:  $\leq 1m\Omega$
- 线径范围: 1.5-10mm<sup>2</sup>(16-8 AWG)
- 可插拔次数:  $\geq 500$

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 40A
- Contact resistance:  $\leq 1m\Omega$
- Wire gauge: 1.5-10mm<sup>2</sup>(16-8 AWG)
- Mating cycles:  $\geq 500$



						表面处理 Finish	-		图号 Drawing No.	-
						材料 Material	-		产品代号 Part Code	CCSM-XX
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date			产品料号 Part No.	-
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name
绘图 Drawn			标准化 Stand.	-	-	2:1	V1.0	-	-	-
审核 Checked										
工艺 Process	-	-	批准 Approved							
								All Dimensions in mm Original Size DIN A 4		